

# FLOORING ADHESIVE

READY TO USE ADHESIVE FOR FLOOR COVERINGS, LINOLEUM AND WALL CORK.



## PRODUCT DESCRIPTION

Ready to use adhesive for floor coverings, linoleum and wall cork. Water-based adhesive.

## FIELD OF APPLICATION

For fixing floor coverings and carpet tiles with jute, felt or textile back, linoleum and wall cork on porous surfaces such as cement, concrete and wood.

## PROPERTIES

- Easy to use
- Solvent free
- Not moisture-resistant

## PREPARATION

**Working conditions:** Do not use at temperatures below +15°C and/or a relative air humidity above 65%.

**Preliminary surface treatment:** Surface should be porous, level, solid, and permanently free of grease and dust. Damaged and unlevel surfaces should be levelled first.

**Tools:** Bison Glue spreader no. 2

## APPLICATION

**Dilute:** If thickened, adhesive may be diluted with water.

**Coverage:** 2-3 m<sup>2</sup>/kg

### Directions for use:

Apply adhesive evenly to surface (clean, dry and free of grease) using a Bison glue spreader no. 2. Put floor covering, linoleum or wall cork into the wet adhesive within 15 minutes and press or roll firmly. Adjustments can be made during approx. 15 minutes. Connection can be submitted to a charge after approx. 24-48 hours.

**Open time:** approx. 15 minutes

**Stains/residue:** Remove wet stains immediately with water. Soak dry residue in warm water for a long time and then chip off with a putty knife.

**Points of attention:** In case of bonding to wooden surfaces, seams may become apparent. Connection should not be submitted to a charge prior to curing. Adhesive smell will disappear provided that surface is dry.

## CURE TIMES

**Dry/Cure time:** approx. 24-48 hours

\* Curing time may vary depending on a.o. surface, product quantity used, humidity level and ambient temperature.

## TECHNICAL PROPERTIES

**Moisture resistance:** Nil

**Temperature resistance:** -20°C to 50°C

**Chemicals resistance:** Good

## TECHNICAL SPECIFICATIONS

**Chemical base:** Sulfite lye

**Viscosity:** Pasty

**Solid contents:** approx. 79 %

**Density:** approx. 1.61 g/cm<sup>3</sup>

## STORAGE CONDITIONS

At least 24 months after date of manufacture. Store in a well-closed packaging in a cool and frost-free place.